

## TUBI SS API 5L GR.B - ASTM A 106 GR.B

diametro				
nominale pollici	esterno mm	spessore mm	n° di schedula	peso Kg / Mt
3/8"	17,1	2,31	40	0,849
		3,20	80	1,100
1/2"	21,3	2,77	40	1,270
		3,73	80	1,620
		4,78	160	1,950
3/4"	26,7	2,87	40	1,680
		3,91	80	2,190
		5,56	160	2,890
1"	33,4	3,38	40	2,500
		4,55	80	3,230
		6,35	160	4,230
1 1/4"	42,2	3,56	40	3,380
		4,85	80	4,470
		6,35	160	5,600
1 1/2"	48,3	3,68	40	4,050
		5,08	80	5,410
		7,14	160	7,240
2	60,3	3,91	40	5,440
		5,54	80	7,480
		8,74	160	11,110
		11,07	XXS	13,450
2 1/2"	73,0	5,16	40	8,620
		7,01	80	11,410
		9,52	160	14,910
		14,02	XXS	20,410
3"	88,9	5,49	40	11,290
		7,62	80	15,270
		11,13	160	21,330
		15,24	XXS	27,670
4"	114,3	6,02	40	16,070
		8,56	80	22,310
		11,13	120	28,300
		13,49	160	33,530
		17,12	XXS	41,020

diametro				
nominale pollici	esterno mm	spessore mm	n° di schedula	peso Kg / Mt
5"	141,3	6,55	40	21,780
		9,52	80	30,950
		12,70	120	40,280
		15,88	160	49,090
		19,05	XXS	57,420
6"	168,3	7,11	40	28,260
		10,97	80	42,560
		14,27	120	54,200
		18,26	160	67,550
		21,95	XXS	79,180
8"	219,1	6,35	20	33,310
		7,04	30	36,790
		8,18	40	42,530
		10,31	60	53,090
		12,70	80	64,630
10"	273	6,35	20	41,770
		7,80	30	51,000
		9,27	40	60,290
		12,70	60	81,540
		15,09	80	95,970
12"	323,8	18,26	100	114,740
		6,35	20	49,720
		8,38	30	65,200
		9,52	STD	73,820
		12,70	XS	97,440
14"	355,6	14,27	60	108,960
		17,48	80	132,010
		5,33	10	46,070
		7,92	20	67,940
		9,52	30	81,280
16"	406,4	12,70	XS	107,380
		15,09	60	126,680
		19,05	80	158,080
		23,83	100	194,900
		6,35	10	62,630
		7,92	20	77,860
		9,52	30	93,210
		12,70	40	123,290
		16,66	60	160,120
		21,44	80	203,480